

# **CERTIFICATE OF ACCREDITATION**

This is to attest that

## **GN TECHNOLOGIES DBA PRECISION LABORATORIES**

664 EAST RANCHO VISTA BOULEVARD PALMDALE, CALIFORNIA 93550 U.S.A.

**Calibration Laboratory CL-232** 

has met the requirements of AC204, *IAS Accreditation Criteria for Calibration Laboratories*, and has demonstrated compliance with ISO/IEC Standard 17025:2017, *General requirements for the competence of testing and calibration laboratories*. This organization is accredited to provide the services specified in the scope of accreditation.

Effective Date January 31, 2024

Expiration Date September 1, 2025



President

Visit www.iasonline.org for current accreditation information.

## SCOPE OF ACCREDITATION

International Accreditation Service, Inc.

3060 Saturn Street, Suite 100, Brea, California 92821, U.S.A. | www.iasonline.org

### **GN TECHNOLOGIES DBA PRECISION LABORATORIES**

www.thecallab.com

#### Contact Name Terrance Norris

Contact Phone + 1 661-265-6500

Accredited to ISO/IEC 17025:2017

Effective Date January 31, 2024

MEASURED QUANTITY or DEVICE TYPE CALIBRATED	RANGE	UNCERTAINTY <sup>1,2</sup> (±)	CALIBRATION METHOD OR PROCEDURE, STANDARD EQUIPMENT (OPTIONAL)
Mechanical			
Gas Flow Controllers/Meters	0 cm <sup>3</sup> /min to 250 cm <sup>3</sup> /min 0 cm <sup>3</sup> /min to 6000 cm <sup>3</sup> /min 0 L/min to 30 L/min	2.2 cm <sup>3</sup> /min 49 cm <sup>3</sup> /min 0.25 L/min	Gilibrator Flow Standard – by direct comparison method

#### **CALIBRATION AND MEASUREMENT CAPABILITY (CMC)\***

<sup>1</sup>The uncertainty covered by the Calibration and Measurement Capability (CMC) is expressed as the expanded uncertainty having a coverage probability of approximately 95 %. It is the smallest measurement uncertainty that a laboratory can achieve within its scope of accreditation when performing calibrations of a best existing device. The measurement uncertainty reported on a calibration certificate may be greater than that provided in the CMC due to the behavior of the calibration item and other factors that may contribute to the uncertainty of a specific calibration.

<sup>2</sup>When uncertainty is stated in relative terms (such as percent, a multiplier expressed as a decimal fraction or in scientific notation), it is in relation to instrument reading or instrument output, as appropriate, unless otherwise indicated.

\* If information in this CMC is presented in non-SI units, the conversion factors stated in NIST Special Publication 811 "Guide for the Use of the International System of Units (SI)" apply.

Effective Date January 31, 2024 Page 2 of 2 IAS/CL/100-3